

Medium

## OBELIX S3

### Comfortable high-quality safety sneaker

Stylish safety sneaker with sporty elements. A lightweight design and outstanding climate characteristics ensure that the Obelix stands out from the crowd. The shock-absorbing outsole and removable insole ensure maximum comfort. Thanks to the high SRC slip resistance the safety sneaker prevents you from slips, trips, and falls. As a result: maximum comfort and reliable safety.

Upper	Waterproof Suede
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	Rubber
Toecap	Aluminium
Safety standard	S3 / ESD, SRC
Size range	EU 35-48 / UK 3.0-13.0 US 3.0-13.5 / CM 23.0-31.5
Sample weight	0.597 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



BLK



BLU



#### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



#### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



#### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



#### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



#### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



#### Aluminum toecap

Aluminum toecaps bring the resistance of steel toes to a lighter weight (30-50% lighter than steel). Alloy toes have a low profile, which makes them ideal for sportive safety shoes. The average weight of the aluminum cap is about 50/60 gr.

Industries:

Automotive, Catering, Cleaning, Construction, Food & beverages, Logistics, Industry, Uniform

Environments:

Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Waterproof Suede			
	Upper: permeability to water vapor	mg/cm²/h	4.06	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	33.9	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	6.4	≥ 2
	Lining: water vapor coefficient	mg/cm²	52.6	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Rubber			
	Outsole abrasion resistance (volume loss)	mm³	119.8	≤ 150
	Outsole slip resistance SRA: heel	friction	0.39	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.18	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	2.89	0.1 - 100
	Heel energy absorption	J	25.1	≥ 20
Toecap	Aluminium			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	NA
	Impact resistance toecap (clearance after impact 200J)	mm	18.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	18.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com