

Light

CADOR S1P

Sporty low-cut ESD safety shoe

Cador is a low-cut S1P safety shoe made of mesh, a slip resistant outsole that fulfills electrostatic discharge requirements and a steel toe cap and anti-penetration sole. Its main assets? Good quality in exchange for a competitive price. High wearing comfort – with optimum shock absorption in heel and forefoot - that puts an end to aching feet at the end of the working day. And a sporty and fun design with fashionable color accents, making it an ideal fit for both men and women. Of course with the same quality standards that Safety Jogger always guarantees and that allow you to work in complete safety. Ideal for light applications in the automotive, construction, industrial, logistics and engineering sector

Upper	Mesh
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Safety standard	S1P / ESD, SRC
Size range	EU 35-48 / UK 3.0-13.0 US 3.0-13.5 / CM 23.0-31.5
Sample weight	0.575 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



Airblaze technology

Moisture and temperature management system to provide optimum wearer comfort by keeping your feet dry and comfortable.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



BLU



GRN



LGR



PNK



RED



YEL

Industries:

Automotive, Construction, Food & beverages, Logistics, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Mesh			
	Upper: permeability to water vapor	mg/cm²/h	3.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	41	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	61.1	≥ 2
	Lining: water vapor coefficient	mg/cm²	490	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	59	≤ 150
	Outsole slip resistance SRA: heel	friction	0.30	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.24	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	73	0.1 - 100
	Heel energy absorption	J	24	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	NA
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com